

AIR HEATERS



LH120 – LH530



LH620 – LH930

Characteristics:

- ▶ For wall mounting and ceiling mounting
- ▶ Operation with outside air, mixed air and recirculating air possible
- ▶ For heating and ventilating
- ▶ Including air outlet grills
- ▶ Heat exchanger made of Cu/Alu
- ▶ Fans with blade rotor

These units are of compact construction and can easily be mounted anywhere. They are designed both for mounting at walls or at the ceiling. They operate via the pipe system of your central heating. The large range offers heaters from 10 – 118 kW of heat output.

The integrated heat exchanger is made from copper/aluminium for hot water as a heating medium. The units have protection class IP54.

The multi-stage adjustable fans are perfect for the multitude of different

needs on site. They assure draught-free, area-wide and comfortable distribution of heat and air.

In order to calculate your requirements exactly, the Kroll consultant team is at your disposal.

■ Large power range

A wide range of models with a multi-stage fan permits an optimal solution to your requirements.

■ Special versions

On request, we can also supply units that use steam as heating medium or versions with explosion proof motors as well as units suitable for operation in stables.

■ Suitable for every application

They can easily be changed from wall mounting to ceiling mounting, which makes them extremely versatile.

■ Low noise level

No noise pollution due to quiet operation.

■ Elegant design

Besides the powdered version LH (RAL 7035), all models are also available as version LH-X with stainless steel casing.

■ Wide range of accessories

With the right accessories, a comfortable room climate becomes the most natural thing.

Delivered units may differ from the pictures.